

10/733,975

RECEIVED
CENTRAL FAX CENTER

AUG 27 2007

CLAIMS

1. (Original) A system for securing signals in a communications system comprising:
- first means for incorporating a code within a signal;
 - second means for employing said code to decode said signal; and
 - 5 third means for selectively preventing detection by said second means of a subsequent signal employing said code.
2. (Original) The system of Claim 1 wherein said third means includes a predetermined delay after receipt of said signal by said second means, said predetermined delay sufficient to prevent detection by said second means of said subsequent signal employing said code, and wherein said code is a function of a time
- 5 value associated with said signal, and wherein said subsequent signal incorporating said code lacks a corresponding accurate time value due to said predetermined delay, thereby disabling detection of said subsequent signal via said second means.
3. (Original) The system of Claim 2 wherein said second means includes a receiver having a delay buffer, said delay buffer sufficient to add said predetermined delay to said signal before detection by said second means.
4. (Original) The system of Claim 3 wherein said receiver has a correlator that employs said code to detect said signal.
5. (Original) The system of Claim 4 wherein said predetermined delay is longer than a search window employed by said correlator.

10/733,975

6. (Original) The system of Claim 4 wherein said receiver incorporates a clock whose time is selectively adjustable via a received signal and not user-adjustable via said receiver.

7. (Original) The system of Claim 6 wherein said receiver includes means for receiving a time value from said clock, adding a user-adjustable modification thereto, and outputting an adjusted time value in response thereto.

8. (Original) The system of Claim 7 wherein said receiver incorporates a clock whose time is selectively adjustable via a received authenticated signal and user-adjustable only if said code is reset or erased.

9. - 14. (Canceled)

15. (Original) An efficient receiver comprising:

first means for receiving an encoded signal;

second means for detecting and decoding said encoded signal via a replica of a code or inverse thereof employed to encode said encoded signal, said second means

5 characterized by a search window; and

third means for selectively delaying said encoded signal beyond said search window prior to decoding by said second means.

16. (Original) A spread spectrum communication system having reduced noise comprising:

first means for encoding a signal via a predetermined code and transmitting a corresponding encoded signal;

5 second means for receiving said encoded signal said second means including a receiver that employs a replica of said predetermined code and a search window to detect said encoded signal; and

10/733,975

third means for selectively delaying said encoded signal beyond said correlation window.

17. (Currently Amended) A method for preventing spoofing of a signal comprising the steps of:

incorporating a cryptographic code within said signal, said cryptographic code a function of a time value associated with said signal and

- 5 employing said cryptographic code to detect said signal after a predetermined delay after receipt of said signal via a [said] second means, said predetermine delay sufficient to prevent detection by said second means of a subsequent signal employing said cryptographic code.